

Before you purchase your next waterproofer, compare labels.

COMPETITORS' PRODUCTS -

Cabot's Deck Sealer, Behr's Waterproofer, Thompson's Water Seal Multi Surface, Sikken's Deck Sealer

Information below is taken directly from one or more of these competitors' labels.

Notice: Cancer Causing Chemicals

This product contains a chemical known to the state of California to cause cancer and birth defects, or other reproductive harm.

Notice: Brain Damage

Contains solvents which can cause permanent brain and nervous system damage.

Cautions

- Flammable and combustible
- Contains petroleum distillates
- This product contains a maximum of 550 grams of Volatile Organic Compounds (VOCs)
- Wear a vapor respirator during spray applications

Surface Protection Period

Clear stains: 1 year
Other tinted stains: 2 to 4 years

Application Restrictions

Do not apply when air or surface temperature is below 50°F or may fall below 50°F for 48 hours after application.

Streaking/Color Change

If not applied carefully and evenly these products can streak. Some of these products cause a color change.

Clean Up/Disposal

Clean brushes and containers with mineral spirits. Immediately after use place rags, steel wool or waste in a sealed, water filled, metal container.

Danger

Rags, steel wool or waste soaked with decking stain may spontaneously catch fire if improperly stored.

Tinting

Decking stains neutral base and deep base must be tinted with compatible universal colorant.

Other

- These products contain petroleum distillates and VOCs and will harm fish, pets, livestock, plants and people.
- These products sit on the surface and wear away more quickly, requiring regular reapplication.
- These products leach out and will harm the environment.

SEAL-ONCE™

Seal-Once

Does not contain any chemicals known to the state of California to cause cancer and birth defects, or other reproductive harm.

Seal-Once

Does not contain any solvents which can cause brain, nervous system or any other system damage.

Seal-Once

- Non-flammable, non-combustible
- Does not contain petroleum distillates
- Contains zero Volatile Organic Compounds (VOCs)
- Wear a dust mask during spray applications

Seal-Once

Clear: up to 6 years on horizontal surfaces; Tinted: up to 6 years on horizontal surfaces; And up to 10 years on vertical surfaces

Seal-Once

Can be applied at any temperature above 35°F

Seal-Once

Will not streak or change wood color to orange or any other color.

Seal-Once

Clean brushes and containers with warm soapy water and reuse.

Seal-Once

Non-flammable or combustible; Wash rags, steel wool, etc. in warm soapy water and reuse

Seal-Once

Seal-Once tinted formulas are applied directly from the container.

Seal-Once

- Will not harm fish, pets, livestock, plants or people when applied according to the label recommendations.
- Penetrates surfaces up to 3/8" depending on porosity.
- Seal-Once does not leach out or become hydrolytically unstable, therefore, it is safe to use over water.